


Size	Ø40mm
Housing	Aluminum
Impeller	Aluminum
Motor	AC Shaded Pole Type
Operating Temp.	0°C ~+45°C
Insulation	Class A


Model Number	Size (mm)			Voltage (V)	Frequency (Hz)	Current (A)	Power (W)	Speed (RPM)	Air Flow (CFM)	Pressure (mmH2O)	Noise dB(A)	Weight (g)
	A	B	C									
CA04030V11_HWM	310	320	370	120	50/60	0.15/0.13	11/10	2600/2800	35/39	1.9/2.4	30/34	560
CA04030V22_HWM				230	50/60	0.09/0.07	11/9	2600/2800	35/39	1.9/2.4	30/34	
CA04035V11_HWM	360	370	425	120	50/60	0.15/0.13	10/9	2500/2400	49/46	2.0/2.6	33/31	600
CA04035V22_HWM				230	50/60	0.09/0.07	12/11	2500/2400	49/46	2.0/2.6	33/31	
CA04040V11_HWM	410	420	475	120	50/60	0.23/0.21	17/16	2400/2200	74/70	2.1/2.6	37/35	730
CA04040V22_HWM				230	50/60	0.10/0.09	13/13	2400/2200	74/70	2.1/2.6	37/35	

_ for B / S = Ball Bearing / Sleeve Bearing


CA04009



CA04015



CA04019



CA04029

